



AVAILABLE ROCK TRAILER MODELS

- 15T** (15 ton / 13 tonne)
- 18T** (18 ton / 16 tonne)
- 22T** (22 ton / 20 tonne)
- 26T** (26 ton / 24 tonne)
- 40T** (40 ton / 36 tonne)

STANDARD FEATURES

Highway Stub Axles – ease of maintenance and parts availability

Rubber Ride Hitch – dampens vibrations in the tongue when road travelling

Single Multi Stage Hydraulic Lift – reduces oil capacity requirement

- 15T = 21L (5.5 USG)
- 18T = 25L (6.6 USG)
- 22T = 29L (7.8 USG)
- 26T = 36.8L (9.8 USG)
- 40T = 57.9L (15.4 USG) *30.6L (6.73 USG) with patented slave cylinder option installed*

Hardox Steel Body – not just the floor!

- 15T – 22T = 3/16" thickness
- 26T – 40T = 1/4" thickness

Patented "Up and Over" Tailgate

Road Lights

Front and Rear Mud Flaps

Tapered Body - reduces drag on the sides when dumping - load ejects sooner at lower dump height.

AVAILABLE UPGRADE OPTIONS

Front Swivel Hitch - offered in a 1.5" ID or a 2" ID

Tire Options

- | | | |
|-----------|------------------|---------------|
| Model 15T | - 550/45-22.5 BP | |
| Model 18T | - 560/45R22.5 | |
| Model 22T | - 560/60R22.5 | - 710/45R22.5 |
| Model 26T | - 710/50R26.5 | - 800/45R26.5 |
| Model 40T | - 750/60R30.5 | - 850/50R30.5 |

BearClaw

			15T	18T	22T	26T	40T
	Load Capacity	Pounds	28,600	35,200	44,000	52,800	74,800
		KG	13,000	16,000	20,000	24,000	34,000
A	Overall Length	Inch	209	235	258	283	341
B	Overall Height	Inch	92	92	116	119	133
C	Max Height (Tipped)	Inch	186	202	232	252	295
D	Tongue Length	Inch	63	67	75	88	87
E	Overall Width	Inch	99	99	110	120	128
	Struck Volume (Standard)	Cubic Feet	233	288	350	480	675
		Cubic Meter	6.6	8.15	9.91	13.59	19.11
	Heaped Volume (35 deg heap)	Cubic Feet	313	360	435	582	795
		Cubic Meter	8.86	10.2	12.3	16.5	22.5
	Empty Tongue Weight	Pounds	605	630	1400	2100	2300
		KG	275	286	635	953	1043
	Approximate Weight	Pounds	6,400	9,800	13,800	18,100	26,200
		KG	2900	4,445	6,260	8,210	11,884

