



AVAILABLE SILAGE TRAILER MODELS

1440 (1400 cu.ft. / 40 cu.m.)

1850 (1800 cu.ft. / 50 cu.m.)

2260 (2200 cu.ft. / 60 cu.m.)

STANDARD FEATURES

Highway Stub Axles – ease of maintenance and parts availability

Rubber Ride Hitch – dampens vibrations in the tongue when road travelling

Single Multi Stage Hydraulic Lift – reduces oil capacity requirement

- 1440 = 36.8L (9.8 USG)
- 1850 = 43.8L (11.7 USG)
- 2260 = 57.9L (15.4 USG) *30.6L (6.73 USG) with available slave cylinder option installed*

“Drop Down” Side Extensions - allows for quick shifting between silage and grain hauling

Hydraulic Drop Down Front Grill

Hydraulic Jack

Road Lights

Front and Rear Mud Flaps

Single Grain Door kit – installed on all tailgates for discharging grain, wheat, dry corn, etc

Tapered Body Design - helps to reduce drag on the sides when dumping - the load ejects sooner and at a lower dump height.

AVAILABLE UPGRADE OPTIONS

Extra Grain Door Kit – includes two additional grain doors with chutes installed in tailgate

Rear Bolt on Hitch – installed at rear of frame for light duty towing behind the trailer (includes pre-wired 7-pin road light plug)

Cat 4 Front Swivel Hitch - offered in a 1.5” ID or a 2” ID

Wheel Packages	BASE	RECOMMENDED	UPGRADE
Model 1440	– 650/55R26.5	- 710/50R26.5	- 800/45R26.5
Model 1850	– 710/50R26.5	- 800/45R26.5	- 850/40R26.5
Model 2260	– 750/60R30.5	- 850/50R30.5	



			1440	1850	2260
	Load Capacity	Pounds	44,000	52,800	61,600
		KG	20,000	24,000	28,000
A	Overall Length	Inch	378	397	397
B	Overall Height	Inch	153	155	162
C	Overall Height (Extensions Down)	Inch	117	120	128
D	Overall Height Tipped	Inch	322	342	351
E	Overall Height Tipped (Extensions Down)	Inch	300	322	330
F	Tongue Length	Inch	92	92	92
G	Overall Width	Inch	118	121	133
	Grain Volume	Bushels	730	880	1020
	Silage Volume	Cubic Foot	1,412	1,765	2,118
		Cubic Meter	40	50	60
	Empty Tongue Weight	Pounds	1,780	2,220	2,000
		KG	807.4	1,007	907
	Approximate Weight	Pounds	17000	20000	24000
		KG	7,711	9,071	10,886

